

WHAT IS CLAIMED IS:

1. A temperature compensating circuit for compensating an operation of an electronic circuit having a temperature characteristic, comprising:

5 temperature-detecting means for detecting an ambient temperature of the electronic circuit; and temperature compensation control means comprising:

10 correction data storage means for storing correction data generated from the detection characteristic of the temperature-detecting means and the temperature characteristic of the electronic circuit so as to correct a detection error contained in the detection characteristic and the temperature characteristic; and

15 correction processing means for correcting the operation of the electronic circuit on the basis of the ambient temperature detected by the temperature-detecting means and the composite correction data stored in the correction data storage means.

2. A temperature compensating circuit for compensating an operation of an electronic circuit having a temperature characteristic, comprising:

25 temperature detecting means for detecting an ambient temperature of the electronic circuit; and temperature compensation control means; wherein said temperature compensation control

Sub
a1

means includes first storage means for storing first correction data generated to correct a detection error contained in the temperature characteristic of the temperature detecting means, second storage means for storing second correction data corresponding to the first stored correction data generated from the temperature characteristic of the electronic circuit so as to correct the temperature characteristic of the electronic circuit, and correction processing means for correcting the operation of the electronic circuit based on the ambient temperature detected by said temperature detecting means, the first correction data stored in said first storage means and the second correction data stored in said second storage means.

3. A temperature compensating circuit for compensating an operation of an electronic circuit having a temperature characteristic, comprising:

temperature detecting means having a detection characteristic and for detecting an ambient temperature of the electronic circuit; and

temperature compensating control means comprising:

first storage means for storing a corrected temperature corresponding to the detected ambient temperature, generated to compensate detection errors, each being a difference between a value actually detected by the temperature-detecting means and a value expected from the detection

Sub
a1

characteristic of the temperature detecting means;
second storing means for storing an operation
data of the electronic circuit corresponding to a
corrected temperature; and

5 correction processing means for selectively
reading, from the first storage means, a corrected
temperature corresponding to the ambient
temperature detected by the temperature detecting
means, and for correcting the operation of
10 electronic circuit on the basis of the corrected
temperature and the stored operation data of the
electronic circuit corresponding to the corrected
temperature.

15 4. A temperature compensating circuit for
compensating an operation of an electronic circuit
having a temperature characteristic, comprising:

temperature detecting means having a detection
characteristic and designed to detect an ambient
temperature of the electronic circuit; and

20 temperature compensation control means comprising:

first storage means for storing corrected
temperatures each corresponding to the detected
ambient temperature, on the basis of a difference
between one representative value actually detected
25 by the temperature-detecting means and a value
corresponding to the representative value and
expected from the detection characteristic of the

10

Sub
a1

temperature-detecting means;

second storing means for storing an operation data of the electronic circuit corresponding to a corrected temperature; and

5 correction processing means for selectively reading, from the first storage means, a corrected temperature corresponding to the ambient temperature detected by the temperature detecting means, and for correcting the operation of
10 electronic circuit on the basis of the corrected temperature and the stored operation data of the electronic circuit corresponding to the corrected temperature.

Sub
a1
15 5. A temperature compensating circuit for compensating an operation of an electronic circuit having a temperature characteristic, comprising:

temperature detecting means having a detection characteristic and designed to detect an ambient temperature of the electronic circuit; and

20 temperature compensation control means comprising:

first storage means for storing difference data representing a difference between one representative value actually detected by the temperature-detecting means and a value
25 corresponding to the representative value and expected from the detection characteristic of the temperature detecting means;

second storing means for storing an operation data of the electronic circuit corresponding to a corrected temperature; and

5 correction processing means for obtaining a corrected temperature on the basis of the detected ambient temperature and the difference data stored in the first storage means, said corrected temperature corresponding to the ambient temperature detected by the temperature detecting means, and for correcting the operation of electronic circuit on the basis of the corrected temperature and the stored operation data of the electronic circuit corresponding to the corrected temperature.

10
Sub 91
15 6. A temperature compensating circuit for compensating an operation of an electronic circuit having a temperature characteristic, comprising:

temperature detecting means having a detection characteristic and designed to detect an ambient
20 temperature of the electronic circuit; and

temperature compensation control means comprising:

first storage means for storing temperatures differences obtained by dividing a range of temperatures to be detected, into a plurality of
25 temperature sub-ranges, each difference between a representative value actually detected by the temperature-detecting means in one temperature

sub-range and a value corresponding to the representative value and expected from the detection characteristic of the temperature-detecting means;

5 second storing means for storing an operation data of the electronic circuit corresponding to a corrected temperature; and

10 correction processing means for generating, a corrected temperature corresponding to the detected ambient temperature detected on the basis of the stored temperature difference corresponding to the detected ambient temperature, and for
15 correcting the operation of electronic circuit on the basis of the corrected temperature and the stored operation data of the electronic circuit corresponding to the corrected temperature.

7. A temperature compensating circuit for compensating an operation of an electronic circuit having a temperature characteristic, comprising:

20 temperature detecting means having a detection characteristic and designed to detect an ambient temperature of the electronic circuit; and

 temperature compensation control means comprising:

25 first storage means for storing difference data items obtained by dividing a range of temperatures to be detected, into a plurality of temperature sub-ranges and by obtaining differences,

Sub
a1

each between a representative value actually detected by the temperature-detecting means and a value corresponding to the representative value and expected from the detection characteristic of the temperature-detecting means;

second storing means for storing an operation data of the electronic circuit corresponding to a corrected temperature; and

correction processing means for obtaining a corrected temperature on the basis of the ambient temperature detected by the temperature detecting means and the difference data item stored in the first storage means and corresponding to the temperature sub-range in which the ambient temperature detected falls, and for correcting the operation of electronic circuit on the basis of the corrected temperature and the stored operation data of the electronic circuit corresponding to the corrected temperature.

8. The temperature compensating circuit according to claim 2, wherein the first storage means stores corrected temperatures obtained by correcting detection errors contained in the temperature detected by the temperature detecting means, the second storage means stores operation-correcting data items corresponding to the stored corrected temperature, and the correction processing means supplies the detected ambient

5

10

15

20

25

Sub
a.1

temperature value detected by the temperature detecting means, as an address, to the first storage means, thereby to read a corresponding corrected temperature, supplies the corresponding corrected temperature, as an address, to the second storage means, thereby to read a corresponding operation-correcting data, and corrects the operation of the electronic circuit in accordance with the corresponding operation-correcting data.

9. The temperature compensating circuit according to claim 7, wherein said electronic circuit is an oscillator circuit for generating a reference oscillation frequency.

10. An electronic apparatus comprising:
an electronic circuit having a temperature characteristic and designed to perform an operation;
a temperature-detecting circuit for detecting an ambient temperature of the electronic circuit; and
a temperature compensation circuit comprising:
correction data storage means for storing correction data generated from the detection characteristic of the temperature-detecting circuit and the temperature characteristic of the electronic circuit so as to correct a detection error contained in the detection characteristic and the temperature-detecting circuit; and
correction processing means for correcting the operation of the electronic circuit on the

basis of the ambient temperature detected by the temperature-detecting circuit and the composite correction data stored in the correction data storage means.

5 11. The electronic apparatus according to claim 10,
wherein the electronic apparatus includes a radio unit
having an oscillator circuit, and a control circuit for
controlling the operation of said radio unit, said
temperature detecting circuit is provided in said radio
unit, said temperature compensating circuit is provided
10 in said control circuit to temperature-compensate the
operation of said oscillator circuit based on the
ambient temperature detected by said temperature
detecting circuit and the composite correction data
15 stored in an internal memory of said control circuit.

12. An electronic apparatus comprising:

an electronic circuit having a temperature
characteristic and for detecting an operation;

20 a temperature-detecting circuit having a detection
characteristic and for detecting an ambient temperature
of the electronic circuit; and

a temperature compensation circuit comprising:

25 first storage means for storing corrected
temperatures corresponding to the detected ambient
temperature, generated to correct detection errors,
each being a difference between a value actually
detected by the temperature-detecting circuit and

a value expected from the detection characteristic of the temperature detecting means;

second storing means for storing an operation data of the electronic circuit corresponding to a corrected temperature; and

correction processing means for selectively reading, from the first storage means, a corrected temperature corresponding to the ambient temperature detected by the temperature detecting circuit, and for correcting the operation of electronic circuit on the basis of the corrected temperature and the stored operation data of the electronic circuit corresponding to the corrected temperature.

13. An electronic apparatus comprising:

an electronic circuit having a temperature characteristic and designed to perform an operation;

a temperature-detecting circuit having a detection characteristic and designed to detect an ambient

temperature of the electronic circuit; and

a temperature compensation circuit comprising:

first storage means for storing corrected temperatures each corresponding to the detected ambient temperature, generated on the basis of a

difference between one representative value

actually detected by the temperature-detecting circuit and a value corresponding to the

Sub
at

representative value expected from the detection characteristic of the temperature-detecting circuit;

second storing means for storing an operation data of the electronic circuit corresponding to a corrected temperature; and

correction processing means for selectively reading, from the first storage means, a corrected temperature corresponding to the ambient temperature detected by the temperature detecting circuit, and for correcting the operation of electronic circuit on the basis of the corrected temperature and the stored operation data of the electronic circuit corresponding to the corrected temperature.

14. An electronic apparatus comprising:

an electronic circuit having a temperature characteristic and designed to perform an operation;

a temperature-detecting circuit having a detection characteristic and designed to detect an ambient temperature of the electronic circuit; and

a temperature compensation circuit comprising:

first storage means for storing difference data representing a difference between one representative value actually detected by the temperature-detecting circuit and a value corresponding to the representative value and

expected from the detection characteristic of the temperature detecting circuit;

second storing means for storing an operation data of the electronic circuit corresponding to a corrected temperature; and

correction processing means for obtaining a corrected temperature on the basis of the ambient temperature detected by the temperature detecting circuit and the difference data stored in the first storage means, said corrected temperature corresponding to the ambient temperature detected by the temperature detecting circuit, and for correcting the operation of electronic circuit on the basis of the corrected temperature and the stored operation data of the electronic circuit corresponding to the corrected temperature.

15. An electronic apparatus comprising:

an electronic circuit having a temperature characteristic and designed to perform an operation;

a temperature-detecting circuit having a detection characteristic and designed to detect an ambient temperature of the electronic circuit; and

a temperature compensation circuit comprising:

first storage means for storing temperatures differences obtained by dividing a range of temperatures to be detected, into a plurality of temperature sub-ranges, each difference between a

Sub
a1

representative value actually detected by the temperature-detecting circuit in one temperature sub-range and a value corresponding to the representative value and expected from the detection characteristic of the temperature-detecting circuit;

second storing means for storing an operation data of the electronic circuit corresponding to a corrected temperature; and

correction processing means for generating, a corrected temperature corresponding to the detected ambient temperature detected on the basis of the stored temperature difference corresponding to the detected ambient temperature and for correcting the operation of electronic circuit on the basis of the corrected temperature and the stored operation data of the electronic circuit corresponding to the corrected temperature.

16. An electronic apparatus comprising:

an electronic circuit having a temperature characteristic and designed to perform an operation;

a temperature-detecting circuit having a detection characteristic and designed to detect an ambient temperature of the electronic circuit; and

a temperature compensation circuit comprising:

first storage means for storing difference data items obtained by dividing a range of

5

10

15

20

25

Sah
a

temperatures to be detected, into a plurality of temperature sub-ranges and by obtaining differences, each between a representative value actually detected by the temperature-detecting circuit and a value corresponding to the representative value and expected from the detection characteristic of the temperature-detecting circuit;

second storing means for storing an operation data of the electronic circuit corresponding to a corrected temperature; and

correction processing means for obtaining a corrected temperature corresponding to the ambient temperature detected by the temperature detecting circuit and the difference data item stored in the first storage means and corresponding to the temperature sub-range in which the ambient temperature detected falls, and for correcting the operation of electronic circuit on the basis of the corrected temperature and the stored operation data of the electronic circuit corresponding to the corrected temperature.

17. A radio unit comprising:

a radio circuit for down-converting a received radio signal to an intermediate-frequency signal or a base-band signal and up-converting an intermediate-frequency signal or base-band signal to be transmitted; an oscillator circuit having a temperature

5

10

15

20

25

Sub
a1

characteristic and designed to generate a local oscillation signal for use in down-converting and up-converting signals in the radio circuit;

5 a temperature-detecting circuit for detecting an ambient temperature of the oscillator circuit; and

a temperature-compensating circuit comprising:

10 correction data storage means for storing correction data generated from the detection characteristic of the temperature-detecting circuit and the temperature characteristic of the oscillator circuit so as to correct a detection error contained in the detection characteristic and the temperature characteristic; and

15 correction processing means for correcting the operation of the oscillator circuit on the basis of the ambient temperature detected by the temperature-detecting circuit and the composite correction data stored in the correction data storage means.

20 18. A radio unit comprising:

a radio circuit for down-converting a received radio signal to an intermediate-frequency signal or a base-band signal and up-converting an intermediate-frequency signal or base-band signal to be transmit;

25 an oscillator circuit having a temperature characteristic and designed to generate a local oscillation signal for use in down-converting and

Sub
a1

up-converting signals in the radio circuit;

a temperature-detecting circuit for detecting an ambient temperature of the oscillator circuit; and a temperature-compensating circuit comprising:

5 first storage means for storing corrected temperature corresponding to the detected ambient temperature, generated to compensate detection errors, each being a difference between a value actually detected by the temperature-detecting means and a value expected from the detection characteristic of the temperature detecting circuit;

10

Sub
a1

15

second storing means for storing an operation data of the oscillator circuit corresponding to a corrected temperature; and

20

correction processing means for selectively reading, from the first storage means, a corrected temperature corresponding to the ambient temperature detected by the temperature detecting circuit, and for correcting the operation of oscillator circuit on the basis of the corrected temperature and the stored operation data of the oscillator circuit corresponding to the corrected temperature.

25

19. A radio unit comprising:

a radio circuit for down-converting a received radio signal to an intermediate-frequency signal or a

base-band signal and up-converting an intermediate-frequency signal or base-band signal to be transmit;

an oscillator circuit having a temperature characteristic and designed to generate a local
5 oscillation signal for use in down-converting and up-converting signals in the radio circuit;

a temperature-detecting circuit for detecting an ambient temperature of the oscillator circuit; and

a temperature-compensating circuit comprising:

10 first storage means for storing corrected temperatures each corresponding to the detected ambient temperature, generated on the basis of a difference between one representative value actually detected by the temperature-detecting
15 circuit and a value corresponding to the representative value expected from the detection characteristic of the temperature-detecting circuit;

20 second storing means for storing an operation data of the oscillator circuit corresponding to a corrected temperature; and

25 correction processing means for selectively reading, from the first storage means, a corrected temperature corresponding to the ambient temperature detected by the temperature detecting circuit, and for correcting the operation of oscillator circuit on the basis of the corrected

10
Sub
a1

and the stored operation circuit corresponding to the operation bit comprising:

a circuit for down-converting a received intermediate-frequency signal and up-converting an intermediate-frequency signal to a base-band signal to be received by the radio circuit having a temperature compensating circuit designed to generate a correction signal for use in down-converting the received signal in the radio circuit;

a detecting circuit for detecting a frequency of the oscillator circuit and a compensating circuit compensating the frequency means for storing a difference between the frequency value actually detected by the detecting circuit and a value stored in the representative value memory to the detection characteristic of the detecting circuit;

storing means for storing a correction signal; oscillator circuit corresponding to the correction signal; and

temperature processing means for processing the temperature on the basis of the correction signal.

5

10
Conc
a1

15

20

25

second storing means for storing an operation data of the oscillator circuit corresponding to a corrected temperature; and

correction processing means for obtaining a corrected temperature on the basis of the detected

ambient temperature and the difference data stored in the first storage means, said corrected temperature corresponding to the ambient temperature detected by the temperature detecting circuit, and for correcting the operation of oscillator circuit on the basis of the corrected temperature and the stored operation data of the oscillator circuit corresponding to the corrected temperature.

21. A radio unit comprising:

a radio circuit for down-converting a received radio signal to an intermediate-frequency signal or a base-band signal and up-converting an intermediate-frequency signal or base-band signal to be transmit;

an oscillator circuit having a temperature characteristic and designed to generate a local oscillation signal for use in down-converting and up-converting signals in the radio circuit;

a temperature-detecting circuit for detecting an ambient temperature of the oscillator circuit; and

a temperature-compensating circuit comprising:

first storage means for storing temperatures differences obtained by dividing a range of temperatures to be detected, into a plurality of temperature sub-ranges, each difference between a representative value actually detected by the temperature-detecting circuit in one temperature

5

10

15

20

25

Sub
A1

sub-range and a value corresponding to the representative value and expected from the detection characteristic of the temperature-detecting circuit;

5 second storing means for storing an operation data of the oscillator circuit corresponding to a corrected temperature; and

10 correction processing means for generating, a corrected temperature corresponding to the detected ambient temperature detected on the basis of the stored temperature difference corresponding to the detected ambient temperature, and for correcting the operation of oscillator circuit on the basis of the corrected temperature and the
15 stored operation data of the oscillator circuit corresponding to the corrected temperature.

22. A radio unit comprising:

20 a radio circuit for down-converting a received radio signal to an intermediate-frequency signal or a base-band signal and up-converting an intermediate-frequency signal or base-band signal to be transmit;

25 an oscillator circuit having a temperature characteristic and designed to generate a local oscillation signal for use in down-converting and up-converting signals in the radio circuit;

 a temperature-detecting circuit for detecting an ambient temperature of the oscillator circuit; and

Sub
91

a temperature-compensating circuit comprising:

first storage means for storing difference data items obtained by dividing a range of temperatures to be detected, into a plurality of temperature sub-ranges and by obtaining differences, each between a representative value actually detected by the temperature-detecting circuit and a value corresponding to the representative value and expected from the detection characteristic of the temperature-detecting circuit;

second storing means for storing an operation data of the oscillator circuit corresponding to a corrected temperature; and

correction processing means for obtaining a corrected temperature on the basis of the ambient temperature detected by the temperature detecting circuit and the difference data item stored in the first storage means and corresponding to the temperature sub-range in which the ambient temperature detected falls, and for correcting the operation of oscillator circuit on the basis of the corrected temperature and the stored operation data of the oscillator circuit corresponding to the corrected temperature.

5

10

15

20

Sub
ai